

## MINI DEGASIFIER – E865C SERIES

### SPECIFICATIONS

#### DIMENSIONS:

Height: 46" (1170 mm)  
Width: 23" (585 mm)  
Depth: 23" (585 mm)  
Weight: 275lbs (125kg)

#### STANDARD VOLTAGE:

230V-1PH-60Hz  
(other voltages available on request)

#### SYSTEM PERFORMANCE:

Final water content <10 ppm  
Final gas content <0.25%  
Filter to 1/2 microns nominal 60 US  
Gallons (230 L) per hour flow rate at  
60 Hz  
Viton Seals Standard  
3 kW heater  
"1/2" Kamlock quick connections

Enervac International ULC  
280 Holiday Inn Drive  
Cambridge, Ontario  
Canada  
N3C 1Z4  
(P)1-519-651-1034  
(F)1-519-651-1038


www.enervac.com  
sales@enervac.com



For more  
information  
scan the  
code!

This lightweight Mini Degasifier cart uses the latest high vacuum technology to filter, dehydrate and degasify insulating and dielectric fluids.

The unit is ideally suited for processing oil in pole mounted transformers, bushings, conservators, individual barrels of oil and other similar small fluid amounts.



#### FEATURES:

- Mounted on a convenient cart with 10" (250 mm) pneumatic tires for ease of movement
- Connection provided for optional vacuum controller
- Unattended operation
- Vacuum blank off rating <20 microns (0.025 mbar)
- Uses Enervac's exclusive accelerator elements for high performance
- Unit comes complete with 10-foot (3 m) power cord and hoses